

The Iwatsu ICON Series IX-59DS IP DSS unit was designed to simplify the call processing for attendants, administrative assistants and power users by providing a large, backlit LCD with 30 self-labeling keys. The ICON Series IP DSS includes a layer-2 switch to connect to a PC or other network resource. Up to 60 feature keys across two screens are supported on the the Iwatsu ICON Series IP DSS and can be used for call coverage, direct station selection or other Iwatsu features.



IX-59DS IP DSS

**ICON**VoiceNetworks

## IX-59DS IP DSS

## **Technical Specifications**

3-Position Integrated Pedestal:	Standard	Supported Phones:	Iwatsu ICON Series IX-5810, IX-5910 & IX-5930
Self-Labeling Keys:	30 Keys by 2 Screens; 60 Feature Keys Max	Maximum IX- 59DS per Station:	2
Display:	15-Line, 24-Character Backlit Display	Maximum IX- 59DS per System:	64
Programmable Backlight:	Standard	Maximum Distance:	Ethernet Maximum
Power Supply:	POE or Local Power Connection	Layer-2 Switch:	Standard

Part Number 108565. The products and features described are for illustrative purposes only and are subject to change. Equipment performance and capacities may be affected by system configuration. Interoperability with third party products and/or services may be subject to limitation. Consult your Authorized ICON Voice Networks Dealer to design a system to meet the specific needs of your business. Current product, feature specifications and limitations are available on our web site: www.iconvoicenetworks.com.