

IX-5810 Digital and IX-5910 IP Telephone



IX-5930 IP Telephone



Phone Features

| PHONE TYPE | IX-5810 | IX-5800 | IX-5910 | IX-5930 |
|--|--|---|--|---|
| General Availability | September 1, 2008 | September 1, 2008 | December 1, 2008 | December 1, 2008 |
| ECS Software Version | 5.00 | 5.00 | 5.10 | 5.10 |
| ECS Hardware | IX-16PSUB-2, IX-8PSUB-2 | IX-16PSUB-2, IX-8PSUB-2 | IX-MBU | IX-MBU |
| LCD | 7 lines x 24 characters w/ backlight | 2 lines x 16 characters | 7 lines x 24 characters w/ backlight | 15 lines x 24 characters w/ backlight |
| Display Keys | 10 | 0 | 10 | 30 |
| Feature Keys | 26 plus optional 8ELK | 9 plus optional 9ELK | 26 plus optional 8ELK | 30 |
| Bluetooth Headset Interface | Optional | Not Available | Optional | Optional |
| Notable Features | <ul style="list-style-type: none"> •Paperless Key Label Design •Integrated Directory •Improved Call Log •Improved Forwarding •Improved Conferencing •Omega-Voice VMI (IX-4EVMC) Menu Integration •Ticker Field Display Feature •TOL UC Integration from LCD (V 5.10) | <ul style="list-style-type: none"> •Improved Conferencing •Ticker Field Display | <ul style="list-style-type: none"> •Paperless Key Label Design •Integrated Directory •Improved Call Log •Improved Forwarding •Improved Conferencing •Omega-Voice VMI (IX-4EVMC) Menu Integration •Ticker Field Display Feature •Text Web web page integration to LCD •TOL UC Integration from LCD | <ul style="list-style-type: none"> •100% Paperless Key Label Design •Integrated Directory •Improved Call Log •Improved Forwarding •Improved Conferencing •Omega-Voice VMI (IX-4EVMC) Menu Integration •Ticker Field Display Feature •Text Web web page integration to LCD •TOL UC Integration from LCD |
| 2100 Loop Distance with Optional Station Loop Extender | •Optional | •Optional | •N/A | •N/A |