



## Big Capability for Small Business

Small businesses need a flexible telecommunication system that can easily adapt to your changing and growing needs. The Strata CIX100™ is specifically designed to provide the exact telecommunication features your business requires today, and as it grows in the future. That makes the Strata CIX100 the ultimate cost-effective telecommunication solution to give you the investment protection you need.

Toshiba's expertise makes the Strata CIX100 the optimum solution, whether you need a basic telephone system or advanced capabilities. For example, you can add valuable options like Voice Mail/Auto Attendant/Unified Messaging, Automatic Call Distribution, Voice Over Internet Protocol, StrataNet multiple system networking, FeatureFlex™ adaptability/customization tools, and more to improve your business' overall productivity and customer service.

### SPECIFICATIONS

CIX100 Capacities	64 CO lines/72 station users (112 Universal ports)			
Chassis Measurements Base Cabinet	Width	Height	Depth	Weight
Metric	302 mm	371 mm	259 mm	8.8 kg
English	11.9 in.	14.6 in.	10.2 in.	19.4 lbs.
Chassis Measurements Expansion Cabinet	Width	Height	Depth	Weight
Metric	203 mm	371 mm	259 mm	6.9 kg
English	8 in.	14.6 in.	10.2 in.	15.2 lbs.
Power Supply Unit (PSU)	Initially Built-in (one per cabinet)			
Primary AC Power	Input AC 120VAC, 4.0 amps maximum. AC Frequency Single-phase (48Hz - 62Hz). 100 watts per cabinet (maximum).			
Power Backup	Two or four 12VDC external batteries (80 ampere-hours max.) with ABCS charger can provide power backup operation for 12 - 50 hours depending upon configuration (batteries and ABCS optional).			
Chassis Installation	Wall-mount (preferred) or Table top			
Compliance	Safety: cUL EMC: FCC Part 15 Class A (Subpart A) HAC and Volume Control: FCC Part 68 Network safety: TIA-968-2-A			
IC/FCC Registration	IC PBX: 248-3032A Hybrid: 248-3032A Key: 248-3032A	FCC PBX: CJ6MUL-35931-PF-E Hybrid: CJ6MUL-35930-MF-E Key: CJ6MUL-35929-KF-E		
Operating Temperature	32~104° F (0~40° C)			
Operating Humidity	20~80% relative humidity without condensation			

Storage Temperature	-4 ~ 140° F (-20 ~ 60° C)
Voice Mail Compatibility	Strata Media Application Server, iES32, iES16, IVP8, LVMU, GVMU3
CO Line Compatibility	Analog: Loop or ground start, DID, E&M Digital: T1, ISDN PRI, and BRI IP: Strata Net IP E911: CAMA and ISDN PRI
IP Telephone Compatibility	Toshiba Charcoal Gray MEGACO+ models: <ul style="list-style-type: none"> <li>• IPT2010-SDC: full-duplex speakerphone with 10 programmable buttons, 2-line x 24-character LCD and local central office line interface (future).</li> <li>• IPT2010-SD full-duplex speakerphone with 10 programmable buttons and 2-line x 24-character LCD.</li> <li>• IPT2020-SD full-duplex speakerphone with 20 programmable buttons and 2-line x 24-character LCD.</li> <li>• IPT2008-SDL full-duplex speakerphone with 8 programmable buttons and large 144 x 128 pixel display with HTML support.</li> </ul> 802.3af Power-over-Ethernet compliant. Ethernet switch for PC connection to your IP Network. Uniden UIP 200 SIP Telephone.
Digital Telephone Compatibility	Toshiba 3200-Series Charcoal Gray/Ash White models: <ul style="list-style-type: none"> <li>• DKT3201 (W) single-line telephone.</li> <li>• DKT3210-S (W) speakerphone with 10 programmable buttons.</li> <li>• DKT3220-S (W) speakerphone with 20 programmable buttons.</li> <li>• DKT3210-SD (W) speakerphone with 10 programmable buttons and 2-line x 24-character LCD.</li> <li>• DKT3220-SD (W) speakerphone with 20 programmable buttons and 2-line x 24-character LCD.</li> <li>• DKT3214-SDL (W) speakerphone with 14 programmable buttons and large 8-line x 24-character LCD.</li> </ul>
Analog Device Compatibility	Dealer-supplied standard telephones with or without Caller ID, FAX machines, modems, etc.
Answer Position Options	20-button Add-On Module (Available in Ash White & Charcoal Gray) 60-button DSS/BLF Console (Available in Ash White & Charcoal Gray) Strata PC Attendant Console
User Mobility Options	SoftIPT™ soft phone client on laptop or tablet PC via Wi-Fi. SoftIPT soft phone client on PDA via Wi-Fi. Wireless IP telephone support via Wi-Fi. Cordless digital telephone.
System Administration	Browser-based unified administration of PBX and voice mail functions. eManager™ installation/maintenance for technicians and administrators. eMonitor monitoring of alarm conditions from multiple Strata CIX systems. My Phone Manager™ personal administration for individual users. Traffic measurement reports stored on local SD flash memory card.
Standard System Features	Over 300 standard telephony features to provide the functionality you need.
Advanced Application Options	Add valuable options like Voice Mail/Auto Attendant, Unified Messaging, Automated Speech Recognition, Text-to-Speech, Interactive Voice Response, Automatic Call Distribution and Reporting, Voice Over Internet Protocol, StrataNet multiple system networking, Info Manager™ Web-based telephone applications, FeatureFlex adaptability/customization tools, uniform call distribution, centralized network SMDR*, and more.
Multi-system Networking	StrataNet networking of up to 128 nodes via IP or ISDN PRI.
Feature Customization	FeatureFlex adaptability tools for feature creation/customization.

## Toshiba of Canada Limited, Office Products Group

191 McNabb Street, Markham, Ontario, Canada L3R 8H2 Tel: (905) 470-3500 Fax: (905) 470-3459

18050 Trans Canada Hwy., Kirkland, Quebec, Canada H9J 4A1 Tel: (514) 390-7766 Fax: (514) 390-7770

13551 Commerce Parkway, Suite 110, Richmond, British Columbia, Canada V6V 2L1 Tel: (604) 303-2500 Fax: (604) 303-2501

[www.toshiba.ca/opg](http://www.toshiba.ca/opg)

© 2006 Toshiba of Canada Limited. Office Products Group. Printed in Canada. Strata is a registered trademark of Toshiba Corporation. Specifications subject to change without notice. Some features require optional hardware to support full capabilities.

Part #: TSD-CIX-BR-100-DS-VC-E